

# Single stage Detachable snowblower







# Single stage Detachable snowblower

#### Performance<sup>1</sup>

Capacity: from 4,500 to 5,000 tons/hour Casting distance: up to 55 m (180 ft.)

#### **Dimensions**

Length from attach plate to front:

3,276 mm (129 in.)

Overall width: 2,920 mm (115 in.) Working height: 1,905 mm (75 in.) Weight<sup>2</sup>: 7,258 kg (16,000 lb)

Wheel loader range: 3.50 - 4.50 cu. yd.

#### **Engine**

Power: 388 kW (520 hp)

### Driveline system

Mechanical type equipped with clutch and protecting devices.

#### Hydraulic system

Pump: direct drive
Filter with replaceable cartridge
Valves electro-hydraulic
Controlled by in-cab multifunctional joystick

## Impeller

Impeller casting having a 90° adjustable cast angle: flat from the right to vertical at 90° to the left

Diameter: 1,778 mm (70 in.)

Impeller blades: 6

# Impeller casing

One piece shotgun type

#### **Options**

Engine: 444 kW (595 hp) Female quick attach Hydraulic steering vanes Residential type muffler

#### Notes

- 1. Theoretical and depends on snow conditions.
- 2. With Cat C13 engine, no attachment and no fuel, varies with options.



Due to continuous improvement, the specifications in this brochure may change without prior notice.

For more information, please contact the manufacturer J.A. Larue Inc. or your local distributor.

Deposit brand 1999, all right reserved | Manufactured by: **J.A. Larue Inc.** 660, Lenoir, Québec (Québec) Canada G1X 3W3

Tel: **418-658-3003** | Toll free: 1-877-658-3013 | Fax: 418-658-6799 Web site: **www.jalarue.com** | E-mail: **jalarue@jalarue.com** 

# Your authorized distributor:

Компания « Fortex» Республика Казахстан. 050009. г. Алматы, пр. Гагарина 88/90.

Teπ.: +7-727-317-18-77 e-mail: info@fgco.kz fortexlabmed@gmail.com e-g.ca 171210 Printed in Canada